# MAI \*\* 4SILOMOBIL GRAVITY





MAN ASSISTING INNOVATIONS

# MAI®4SILOMOBIL GRAVITY

# MOBILE MORE QUICKLY AND EASILY

#### THAN EVER BEFORE

Thanks to its practical wheels our conveying unit for gravity silos can be rolled to wherever it's needed from any trailer, station wagon or truck, both quickly and easily. The carrying handles enable problem-free loading and unloading. Even seasoned professionals with years of experience are surprised by this machine concept, which is suitable for all construction sites:

- Reliable, rotary compressor without oil lubrication
   Logical, easy-to-understand operation
  - Service-friendly modular construction

# HOOK IT UP AND IT'S READY TO GO

The logical arrangement of all controls and connections ensures fast and simple setup and operation. No downtimes are necessary for trouble-shooting because any errors are indicated.

### THE ADVANTAGES AT A GLANCE

 Fully automatic phase inverter (direction of motor rotation is always right)

- Fully galvanized frame
  - Diagnosis of errors

#### TECHNICAL DATA

Operating voltage: 400V/3/PE/50Hz

Nominal power: 5,7 kW Fusing: 32 A

L x W x H:  $111 \times 56 \times 82$  cm Air volume approx.:  $100 \text{ Nm}^3/\text{h}$ Volume of pressure: 65 Liter

## WEIGHTS

Conveying unit: 176 kg Pressure reservoir: 83 kg



Г



MAI® International GmbH, Werkstraße 17, 9710 Feistritz/Drau P.O.Box 8, Austria, Europe, E-mail: mai@mai.at, Internet: www.mai.at Tel. +43 (0) 4245/6233-0, Fax +43 (0) 4245/6233-10

© Copyright: MAI® and MAI-PUMP® are registered trademarks of MAI® International GmbH.

MAI® International GmbH reserves the right to alter its machine specfications and descriptions
at any time without prior notice. EN08/2010